
IRONSPIDER
SHEET METAL FABRICATION

PRODUCT SUBMITTAL
EDGE METAL

Drip edge · gravel stop

A nailable top over the deck and a face down the fascia, finished with a drip and a hem. Made to order on IronSpider's brakes from the dimensions on the approved order.

PROFILE (STANDARD SHOWN)



Stretchout at standard: 7 1/2"

DIMENSIONS		STANDARD	RANGE
A	**Nailable top**	3"	1"–8"
B	**Top-to-face angle**	90°	45–135°
C	**Face, total coverage**	4"	1 1/2"–12"
D	**Drip kick**	35°	0–60°
E	**Drip**	1/2"	1/4"–1 1/2"
F	**Hem**	Open 1/2"	len 1/4"–1"

MATERIALS AND GAUGES

Kynar	Painted (Kynar), colors below	24 ga, 22 ga
Galvanized	Galvanized, mill finish	24 ga, 22 ga, 20 ga, 18 ga, 16 ga
Bonderized	Bonderized (paint-ready)	24 ga
Galvalume	Galvalume, mill finish	24 ga
Electro-Galvanized	Electro-galvanized	24 ga
Clad	Membrane-clad (PVC / TPO)	24 ga

KYNAR COLORS

Screen matches: ask for a physical sample before you specify.

- Ash Gray
- Charcoal Gray
- Colonial Red
- Cool Sierra Tan (22 ga)
- Dark Bronze
- Forest Green
- Glacier White
- Graphite Black
- Medium Bronze
- Musket
- Parchment
- Regal Blue
- Saddle Tan
- Sierra Tan
- Terra Cotta (24/22 ga)
- Zinc Gray

CLAD COLORS

- PVC Dark Bronze
- PVC Tan
- PVC White

Testing and code approvals: ask IronSpider about your project's requirements.

PROJECT	
CONTRACTOR	
ARCHITECT / ENGINEER	
SUBMITTED BY	
DATE	

REVIEW

- ☐ Approved
- ☐ Approved as noted
- ☐ Revise and resubmit
- ☐ Rejected

REVIEWED BY / DATE